

Power Distribution

Westell offers an extensive line of fuse, and breaker panels for secondary power distribution. Built in the USA, Westell leads the industry in performance, flexibility, value and product availability.

Features & Benefits

- Ensure protection of site equipment
- Full monitoring of blown fuses or breaker trips and loss of bus power
- Industry standard configurations
- Dual-bus designs for power redundancy
- Dual Voltage Panels (24 or 48Vdc Batteries)

Fuse Panels

- GMT Fuse Panels
- KLM Combination Fuse Panels
- TPA Combination Fuse Panels
- Type 70 Fuse Panels
- TPS Fuse Panels

Breaker Panels

- AC
- DC

Part #	Description	Height	Rack	Cabling Access	Bus	Amps/ Bus	Distribution Capacity						Breaker Limit	Type-70	Max. Oper. Temp.	DC Voltage Supported						Compliance			Dimensions H x W x D (inches)	Panel Weight (lbs)	
							GMT	GMT 20	KLM	TPA	TLS	TPS				±12V	-24V	±24V	-48V	±48V	130V	UL	NEBS	BABA			
							15A	20A	30A	50A	125A	70A															
GMT15 Panels (up to 15A fuses)																											
A90-GMT10-WM	60A, 10 GMT Wall/Cabinet Mount ±10Vdc to ±58Vdc, 3"x6"	3"	Wall	Front	Single	100 / 60	10							+47°C / +70°C	■	■	■	■	■			■	■	■	2.6 x 6 x 2.6	4	
N250110-N-0803	50A, 5/5 GMT, 19"/23", 1RU, Front Access	1RU	19"/23"	Front	Dual	50	5/5							+65°C		■	■	■	■	■			■	■	■	1.75 x 17 x 6.9	8
N250120-N-L9	100A, 10/10 GMT, 19"/23", 1RU	1RU	19"/23"	Rear	Dual	100	10/10							+60°C		■	■	■	■	■			■	■		1.75 x 17 x 10.5	10.2
N250120-N-L33	100A, 10/10 GMT, 19"/23", 2RU, Front Access	2RU	19"/23"	Front	Dual	100	10/10							+60°C		■	■	■	■	■			■	■		3.5 x 17 x 6.9	9.45
N250140-N-L34	100A, 20/20 GMT, 23" only, 1RU	1RU	23"	Rear	Dual	100	20/20							+60°C		■	■	■	■	■			■	■		1.75 x 21 x 11.5	14.55
N250140-NCY-M3	100A, 20/20 GMT, 19"/23", 1RU	1RU	19"/23"	Rear	Dual	100	20/20							+60°C		■	■	■	■	■			■	■		1.75 x 17 x 10.5	11
NPGMT1122	70A, 10 GMT, 19"/23", 1RU, Front Access	1RU	19"/23"	Front	Single	70	10							+65°C		■	■	■	■	■			■	■		1.75 x 17 x 6.9	6.9
GMT20 Panels (up to 15A fuses)																											
NPGMT1125	100A, 10/10 GMT, 20A per position, 19", 1RU, Shallow Depth	1RU	19"	Rear	Dual	100		10/10						+65°C		■	■	■	■	■			■	■	■	1.75 x 17 x 2.5	4.8
NPGMT1107	100A, 10/10 GMT, 20A per position, 19"/23", 1RU	1RU	19"/23"	Rear	Dual	100		10/10						+65°C		■	■	■	■	■			■	■	■	1.75 x 17 x 10.5	9.5
NPGMT1012	100A, 15x15 GMT, 20A per position, 19"/23", 1RU	1RU	19"/23"	Rear	Dual	100		15/15						+65°C		■	■	■	■	■			■	■	■	1.75 x 17 x 10.5	11
NPGMT1305	100A, 10x10 GMT, 20A per position, 23", 1RU, Front Access	1RU	23"	Front	Dual	100		10/10						+70°C	■	■	■	■	■	■			■	■	■	1.75 x 21 x 6.5	8.4
NPGMT1707	125A, 10x10 GMT, 20A per position, 19"/23", 1RU, UL	1RU	19"/23"	Rear	Dual	125		10/10						+70°C		■	■	■	■	■			■	■	■	1.75 x 17 x 10.5	
NPGMT1711	200A, 30 GMT, 20A per position, 19"/23", 1RU	1RU	19"/23"	Rear	Single	200		30						+70°C		■	■	■	■	■			■	■	■	1.75 x 17 x 10.5	8.65
NPGMT1712	125A, 15x15, GMT, 20A per position, 19"/23", 1RU	1RU	19"/23"	Rear	Dual	125		15/15						+70°C		■	■	■	■	■			■	■	■	1.75 x 17 x 10.5	9.05
NPGMT1717	125A, 20x20, GMT, 20A per position, 23", 1RU	1RU	23"	Rear	Dual	125		20/20						+70°C		■	■	■	■	■			■	■	■	1.75 x 21 x 10.5	11.85
NPGMT1722	125A, 10x10, GMT, 20A per position, 19"/23", 2RU, Front Access, UL	2RU	19"/23"	Front	Dual	125		10/10						+70°C		■	■	■	■	■			■	■	■	3.5 x 17 x 6	7.9
NPGMT1727	125A, 15x15, GMT, 20A per position, 19"/23", 2RU, Front Access	2RU	19"/23"	Front	Dual	125		15/15						+70°C		■	■	■	■	■			■	■	■	3.5 x 17 x 6	8.05
NPGMT150D10	150A, 10/10 GMT, 20A, 19"/23", 1RU, Quick-Connect	1RU	19"/23"	Rear	Dual	160/150 140/125		10/10						+50C/+55C +60C/+70C		■	■	■	■	■			■	■	■	1.75 x 17 x 9.5	7.9
NPGMT150D15	150A, 15/15 GMT, 20A, 19"/23", 1RU, Quick-Connect	1RU	19"/23"	Rear	Dual	160/150 140/125		15/15						+50C/+55C +60C/+70C		■	■	■	■	■			■	■	■	1.75 x 17 x 9.5	9.05
NPGMT150D10-FFA	150A, 10/10 GMT, 20A, 19"/23", 2RU, Quick-Connect, Front Access	2RU	19"/23"	Front	Dual	160/150 140/125		10/10						+50C/+55C +60C/+70C		■	■	■	■	■			■	■	■	3.5 x 17 x 4.8	7.9
NPGMT150D15-FFA	150A, 15/15 GMT, 20A, 19"/23", 2RU, Quick-Connect, Front Access	2RU	19"/23"	Front	Dual	160/150 140/125		15/15						+50C/+55C +60C/+70C		■	■	■	■	■			■	■	■	3.5 x 17 x 4.8	8.05

Communication Network Solutions

General Power Distribution Product Order Guide



Part #	Description	Height	Rack	Cabling Access	Bus	Amps/ Bus	Distribution Capacity							Max. Oper. Temp.	DC Voltage Supported						Compliance			Dimensions H x W x D (inches)	Panel Weight (lbs)		
							GMT	GMT 20	KLM	TPA	TLS	TPS	Breaker Limit		Type-70	±12V	-24V	±24V	-48V	±48V	130V	UL	NEBS			BABA	
							15A	20A	30A	50A	125A	70A			10A												
Combination Panels (Mixed fuse types)																											
N215116-N-L31	150A, 4/4 KLM, 4/4 GMT, 19"/23", 1RU	1RU	19"/23"	Rear	Dual	150	4/4		4/4						+60°C		■	■	■	■			■	■	1.75 x 17 x 10.5	13.2	
N215118-N-L11	200A, 4/4 TPA, 5/5 GMT, 19"/23", 1RU, 200A	1RU	19"/23"	Rear	Dual	200	5/5			4/4					+60°C		■		■				■		1.75 x 17 x 10.5	12.8	
N215120-NCY	200A, 4/4 TPA, 6/6 GMT, 19"/23", 1RU, 200A	1RU	19"/23"	Rear	Dual	200	6/6			4/4					+60°C		■	■	■	■			■	■	1.75 x 17 x 12	13	
NPTPA1105	160A, 4/4 TPA, 6/6 GMT, 19"/23", 1RU	1RU	19"/23"	Rear	Dual	160		6/6		4/4					+55°C		■	■	■	■			■	■	1.75 x 17 x 10.5	11.5	
NPTPA1105-V	160A, 4/4 TPA, 6/6 GMT, 19"/23", 1RU, Vertical Inputs	1RU	19"/23"	Rear	Dual	160		6/6		4/4					+55°C		■	■	■	■			■	■	1.75 x 17 x 10.5	11.5	
NPTPA1105-QC	160A, 4/4 TPA, 6/6 GMT, 19"/23", 1RU, Quick Connects	1RU	19"/23"	Rear	Dual	160		6/6		4/4					+55°C		■	■	■	■			■	■	1.75 x 17 x 10.5	11.5	
NPTPA1605	160A, 4/4 TPA, 6/6 GMT, 19"/23", 2RU, Front Access	2RU	19"/23"	Front	Dual	160		6/6		4/4					+70°C		■	■	■	■			■	■	3.5 x 17 x 7.4	12.2	
130Vdc/48Vdc Panels (GMT & Type-70 fuses)																											
130216-F130DHY	16 Position GMT, 10A max. 130Vdc Floating, INP+1, FLTR	2RU	19"/23"	Rear	Single	30	16								+60°C										3.5 x 17 x 10.5	21.45	
130216B-F48DHY	16 Position GMT 10A max, ±48Vdc Floating, INP+1, FLTR	2RU	19"/23"	Rear	Single	30	16								+60°C				■	■					3.5 x 17 x 10.5	21.45	
N250120-N130CY	10/10 GMT, 130Vdc, 19"/23", 1RU	1RU	19"/23"	Rear	Dual	100	10/10								+60°C								■	■	1.75 x 17 x 10.5	11.1	
180108-N-0808	8 Position Type 70, 130Vdc Floating, 19"/23", 1RU	1RU	19"/23"	Rear	Single	80							8		+60°C									■		1.75 x 17 x 10.5	11.15
180108-N48-0808	8 Position Type 70, ±48Vdc Floating, 19"/23", 1RU	1RU	19"/23"	Rear	Single	80							8		+60°C				■	■					1.75 x 17 x 10.5	11.15	
High Amperage Panels & DC Breakers																											
NPTFD1009	125A Demarcation Panel with 4 TFD fuse positions	1RU	19"/23"	Rear	Single	125				4	4				+50°C		■	■	■	■			■	■	1.75 x 17 x 11	13.3	
A90-DCB8X8-R	160A, 8/8 DC Breaker Panel, Isolated A/B, 19"/23", 1RU	1RU	19"/23"	Rear	Dual	160							30A		+70°C		■		■				■	■	1.75 x 17 x 12	10.5	
A90-DCB8X8-FFA	160A, 8/8 DC Breaker Panel, Isolated A/B, 19"/23", 2RU Front Access	1RU	19"/23"	Front	Dual	160/140 130							30A		+50C/+65C +70C		■	■	■				■	■	3.5 x 17 x 9	7.5	
NPDCB400D8	400A, 8/8 DC Breaker Panel, 19"/23", 1RU, Quick-Connect	1RU	19"/23"	Rear	Dual	400/320 240					8/8		65A		+40C/+50C +60C		■	■	■	■			■	■	1.75 x 17 x 15.8	14.8	
NPDCB400D8-ST	400A, 8/8 DC Breaker Panel, 19"/23", 1RU, Screw Terminal	1RU	19"/23"	Rear	Dual	400/320 240					8/8		65A		+40C/+50C +60C		■	■	■	■			■	■	1.75 x 17 x 15.8	14.8	
NPTPA400D8	320A, 8/8 TPA Panel, 19"/23", 1RU, Quick-Connect	1RU	19"/23"	Rear	Dual	320/280 circ air				8/8					+50C/+65C +70C		■	■	■	■			■	■	1.75 x 17 x 15.8	15.2	
NPTPA400D8-ST	320A, 8/8 TPA Panel, 19"/23", 1RU, Screw Terminal	1RU	19"/23"	Rear	Dual	320/280 circ air				8/8					+50C/+65C +70C		■	■	■	■			■	■	1.75 x 17 x 15	15.2	
NPTPA200Q4-ST	140A, 4/4/4/4 TPA Panel, 19"/23", 1RU, Screw Terminal	1RU	19"/23"	Rear	Quad	140/120				4/4/4/4					+50C/+60C		■	■	■	■			■	■	1.75 x 17 x 10.5	12	
A90-DCP10X10	600A, 10/10 DC Breaker/Fuse Panel, 19"/23", 3RU	3RU	19"/23"	Rear	Dual	600				10/10	10/10		100A		+70°C		■	■	■	■			■	■	5.25 x 17 x 7	22.9	
A90-DCP10X10-S	600A, Single 20 DC Breaker/Fuse Panel, 19"/23", 3RU	3RU	19"/23"	Rear	Single	600				20	20		100A		+70°C		■	■	■	■			■	■	5.25 x 17 x 7	23.1	
AC Breaker Panels																											
A90-ACP60B	60A 240V Input CB, Split-Phase, 2x30A 240V Output CB 4x15A 120V Output CB, L1/L2 SPD, 19"/23", 2RU	2RU	19"/23"	Rear	Split-Phase	60							I: 60A O: 30A		+65C								■		3.5 x 17 x 5.3	9	

